Outdoor Kiosk- **H3 Model**

CCL
CREATE CONVENIENT LIFE

Built for the outdoors. Ready for anything



15-inch
Windows

intel INSIDE
intel CORE i3
intel CORE i5

Reliable for outdoor payments and queries, the CCL H3 kiosk withstands extreme temperatures, ensures clear visibility, resists damage, and adapts to any site with easy installation.

Wide-Temperature Design

Operating range from -25°C to 40°C, IP55 dust and water resistant. Performs flawlessly in extreme cold or heat, rain or shine – 24/7 reliability for unattended service..

High-Brightness Screen

1800 nits brightness with automatic ambient light adjustment. Crystal-clear under direct sunlight, comfortably dim at night – smooth and intuitive outdoor operation.

Rugged Protection

IP55 + IK08 dual protection – impact-resistant, damage-proof, and sealed against the elements. Long-term stability reduces maintenance costs and ensures peace of mind.

Flexible Installation

Supports floor-standing or wall-mounting. Minimalist design with LED status indicators. Easily fits plazas, parks, transit hubs, and other outdoor spaces.

Outdoor Kiosk- H3 Model

CREATE CONVENIENT LIFE

System	
Processor	Intel® Core™ i3 1115G4 2C/4T 3.0GHz 6M Intel® Core™ i5 1135G7 4C/8T 2.4GHz 8M
RAM	DDR4 SO-DIMM 1x slot: 4G (Standard) / 8G / 16G
Storage	M.2 SATA 128G / 256G / 512G
OS	Win 10 / Win11 / Linux
Power	
Power Supply	220-230VAC 465W
Display	
Type	15”
Resolution	4:3 , 1024 x 768, 1800nit, 1000:1
Brightness	1800 nits
Touch	True-flat PCAP touch with multi-touch support
I/O Ports	
Serial	6*RS232
USB	8*USB: 2*USB 3.0 - 6*USB 2.0
LAN	1*RJ45, 10 / 100 / 1000 MB
Display port	1*HDMI
Audio	N/A
Standard Components	
Scanner	International first-line barcode scanner, support 1D&2D and scanning mobile phone screen
Light	RGB Color LED Indicator
Physical & Environmental	
Dimension (W x D x H in mm)	450*350*1541mm (Floor-standing) 450*350*776mm (Wall-mounting)
Weight (N. W. in kg)	74kg (Floor-standing) 43kg (Wall-mounting)
Certification	CE / RoHS / IP55
Color	Black
Operating Conditions	-25°C - 40°C, 5%RH - 95%RH
Storage Conditions	-40°C - 70°C, 5%RH - 95%RH



CE RoHS

Customizable payment terminal.



LED indicators for device status display.



Modular design for easy maintenance.



Base unit with independent door access for servicing.



Disclaimer: The product information and specifications are subject to change without prior notice

Qingdao CCL Technology Co., Ltd
Building D2, Floor 26, International Innovation Park
Laoshan District, Qingdao
China

CCL Tech SAS
29, Boulevard de la Paix
78100 Saint-Germain-en-Laye
France