Ticket Vending Machine - HC1

CREATE CONVENIENT LIFE

32-inch outdoor ticketing platform

32-inch Full HD · 1500 cd/m²

Intel Core i5-1235U · 8 GB / 128 GB

Windows 11 / Linux

Optional LTE / 5G



Industrial computing, dual ticket printing, protected power and climate management for outdoor public transport.



Industrial computing

Intel Core i5-1235U, 8 GB RAM and 128 GB SSD, with Windows 11 or Linux.



Dual ticket printing

Two KPM180H printers: around 0.8 seconds per ticket and paper rolls up to 200 metres.



Protected power

OLS1000E UPS with SNMP monitoring and remote power control.



Climate management

Two heaters, humidity control, a dehumidifier and three 24 V fans.

Specifications may vary by configuration. CE marking is based on the manufacturer's EU Declaration of Conformity. The verification covers the tested sample's EMC requirements.

Payment terminals and modems are optional and must be selected locally with your CCL partner to meet local requirements.

Ticket Vending Machine - HC1

CREATE CONVENIENT LIFE

Core system	
Model	CCL-HC1 / CCL-HC
Processor	Intel Core i5-1235U · 12th generation
Memory / storage	8 GB RAM / 128 GB SSD
Operating system	Windows 11 / Linux
System I/O	LAN · 6 × COM · 8 × USB · HDMI · VGA · Wi-Fi
Customer interface	
Display	32-inch · 1920 × 1080 · PCAP · 1500 cd/m² · auto-dimming
Display protection	UV film · IK08 anti-shatter glass · glove touch · −20°C to +70°C
Payment	Optional payment terminal; Verifone UX700 configuration shown
Accessibility / audio	Storm assistive keypad · 2 × 4 Ω / 10 W speakers
Ticketing and communications	
Ticket printers	2 × KPM180H · 0.8 sec/ticket · 200 m paper roll
Connectivity	Ethernet switch · optional LTE/5G modem and antennas
Backup / recovery	UPS-backed power · remote power-control module
Remote monitoring	SNMP-capable UPS · remote operational monitoring
Reliability and power	
Power / UPS	220–240 V AC · 50/60 Hz · 4 A · OLS1000E UPS + SNMP
Climate control	2 heaters · temperature/humidity controller · dehumidifier · 3 × 24 V fans
Protection	RCCB · mains / 10 kV network surge protection · vibration / door sensors
Enclosure	Stainless steel outdoor cabinet · lockable service doors · replaceable filters
CE / EMC conformity	
Verification	ET-26084208EC · test report ET-26084208E
Standards	EN 55032 · EN 55035 · EN IEC 61000-3-2 · EN 61000-3-3



32-inch Full HD · 1500 cd/m²

Intel Core i5-1235U · 8 GB / 128 GB

Windows 11 / Linux

Optional LTE / 5G

Specifications may vary by configuration. CE marking is based on the manufacturer's EU Declaration of Conformity. The verification covers the tested sample's EMC requirements.

Payment terminals and modems are optional and must be selected locally with your CCL partner to meet local requirements.

Qingdao CCL Technology Co., Ltd

Building D2, Floor 26
International Innovation Park
Laoshan District, Qingdao, China

CCL TECH SAS

29, Boulevard de la Paix
78100 Saint-Germain-en-Laye
France

CCL TECH AMERICA LLC

610 E Zack St., Suite 110-3087
Tampa, FL 33602, USA